

## Outdoor Temperature Sensors



**Metal**



**Plastic (RTD/Thermistor)**



**Plastic (0 to 10V/4 to 20 mA)**

### Description

Siemens Outdoor Temperature Sensors monitor and transmit changes in temperature to the HVAC control system. The sensor resistance varies proportionally to the actual temperature being measured.

Units are offered in traditional metal housing as well as modern and aesthetically pleasing polycarbonate housings that blend into today's architectural trends. All are ruggedly designed and built for years of weatherproof, outdoor service.

Multiple output signals are available to ensure compatibility with most common HVAC control systems.

### Features

- Variety of sensing elements.
- Responsive to temperature changes.
- Accurate and reliable indication of temperature.
- Easy installation requires no special tools.

### Specifications

Output Signals	100K $\Omega$ Thermistor 10K $\Omega$ Type 2 Thermistor 1K $\Omega$ @ 32°F Ni RTD 1K $\Omega$ Pt RTD (375a) 1K $\Omega$ Pt RTD (385a) 4 to 20 mA
Accuracy	See Table 1.

**Table 1. Product Ordering Information.**

Housing Material	Output Signal	Measuring Range	Accuracy	Product Number
Metal	100K $\Omega$ Thermistor	-40°F to 150°F (-40°C to 65°C)	$\pm 0.50^\circ\text{F}$ ( $\pm 0.28^\circ\text{C}$ ) @ 77°F (25°C)	536-778
	10K $\Omega$ Type II Thermistor		$\pm 0.4^\circ\text{F}$ ( $\pm 0.2^\circ\text{C}$ ) @ 77°F (25°C)	QAC2030U
	1K $\Omega$ @ 32°F Ni RTD		$\pm 0.72^\circ\text{F}$ ( $\pm 0.4^\circ\text{C}$ ) @ 32°F (0°C)	QAC2020U
	1K $\Omega$ Pt RTD (375a)		$\pm 0.54^\circ\text{F}$ ( $\pm 0.3^\circ\text{C}$ ) @ 32°F (0°C)	544-578
	1K $\Omega$ Pt RTD (385a)			QAC2012U
	4 to 20 mA		-58°F to 122°F (-50°C to 50°C)	$\pm 1.6^\circ\text{F}$ ( $\pm 0.89^\circ\text{C}$ )
Polycarbonate	0 to 10V	-40°F to 158°F (-40 to 70°C)	$\pm 0.81^\circ\text{F}$ ( $\pm 0.45^\circ\text{C}$ ) @ 77°F (25°C)	QAC2030
	10K $\Omega$ Type II Thermistor	-58°F to 158°F (-50°C to 70°C)	$\pm 0.36^\circ\text{F}$ ( $\pm 0.2^\circ\text{C}$ ) @ 32°F (0°C)	QAC22
	1K $\Omega$ @ 32°F Ni RTD	-40 to 158°F (-40 to 70°C)	$\pm 0.54^\circ\text{F}$ (0.3°C) @ 32°F (0°C)	QAC2012
	1K $\Omega$ Pt RTD (385a)	-58° to 122°F (-50° to 50°C)	$\pm 1.6^\circ\text{F}$ ( $\pm 0.9^\circ\text{C}$ )	QAC3171
	4 to 20 mA			

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners.  
© 2016-2022 Siemens Industry, Inc.