

## Powermite 599 Series, MZ Series Zone Control Valves



### Description


The Powermite 599 Series ANSI Class 250 MZ Series valve bodies work with any MZ Series electronic actuator with a 7/32-inch (5.5 mm) stroke. Typical applications include control of hot or chilled water or water-glycol solutions up to 50%. Compatible actuators deliver a minimum of 45 lb (200 N) of force.

### Features




- Direct-coupled universal bonnet
- Female NPT connections and brass trim
- ANSI Leakage Class IV (0.01% of Cv)

### Product Numbers




Use the product numbers in the tables to order the valve and the actuator assembled together. The product number consists of a 3-digit prefix code, a hyphen, and a 5-digit suffix code. The prefix specifies an actuator. The suffix specifies the valve body.






**2-Way, Normally Open Valve and Actuator Assemblies with Brass Trim and Female NPT Connections**

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
				
			Actuator Prefix Code	
			254	255
599-01115	1/2 (15)	0.4 (0.34)	254-01115	255-01115
599-01117	1/2 (15)	0.63 (0.54)	254-01117	255-01117
599-01119	1/2 (15)	1 (0.85)	254-01119	255-01119
599-01121	1/2 (15)	1.6 (1.37)	254-01121	255-01121
599-01123	1/2 (15)	2.5 (2.14)	254-01123	255-01123
599-01126	1/2 (15)	4 (3.42)	254-01126	255-01126
599-01129	3/4 (20)	6.3 (5.38)	254-01129	255-01129
599-01131	1 (25)	10 (8.55)	254-01131	255-01131

**2-Way, Normally Closed Valve and Actuator Assemblies with Brass Trim and Female NPT Connections**

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
				
			Actuator Prefix Code	
			254	255
599-01100	1/2 (15)	0.4 (0.34)	254-01100	255-01100
599-01102	1/2 (15)	0.63 (0.54)	254-01102	255-01102
599-01104	1/2 (15)	1 (0.85)	254-01104	255-01104
599-01106	1/2 (15)	1.6 (1.37)	254-01106	255-01106
599-01108	1/2 (15)	2.5 (2.14)	254-01108	255-01108
599-01110	1/2 (15)	4 (3.42)	254-01110	255-01110
599-01112	3/4 (20)	6.3 (5.38)	254-01112	255-01112
599-01114	1 (25)	10 (8.55)	254-01114	255-01114

**3-Way, Mixing Valve and Actuator Assemblies with Brass Trim and Female NPT Connections**

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
				
			Actuator Prefix Code	
			254	255
599-01132	1/2 (15)	0.4 (0.34)	254-01132	255-01132
599-01133	1/2 (15)	0.63 (0.54)	254-01133	255-01133
599-01134	1/2 (15)	1 (0.85)	254-01134	255-01134
599-01135	1/2 (15)	1.6 (1.37)	254-01135	255-01135
599-01136	1/2 (15)	2.5 (2.14)	254-01136	255-01136
599-01137	1/2 (15)	4 (3.42)	254-01137	255-01137
599-01138	3/4 (20)	6.3 (5.38)	254-01138	255-01138
599-01139	1 (25)	10 (8.55)	254-01139	255-01139

## Technical Data


<b>Line Size</b>	1/2 to 1 inch (15 to 25 mm)	<b>Close-off Ratings</b>	According to ANSI/FCI 70-2 See Table 1.
<b>Body</b>	Globe style, UNS CA 844 bronze or forged brass C37700, ANSI Class 250	<b>Controlled Medium:</b> <b>Two-way valves</b> <b>Three-way valves</b>	Water or water-glycol solutions to 50% Water or water-glycol solutions to 50%
<b>Trim</b>	Brass	<b>Medium Temperature</b>	35°F to 250°F (2°C to 120°C)
<b>Stem</b>	Stainless steel ASTM A582 Type 303, 7/32-inch (5.5-mm) stroke	<b>Max. Differential Pressure for Modulating Service:</b> <b>Liquid (2w and 3w)</b>	25 psi (173 kPa) Cv <1 = >50:1, Cv >1 = >100:1
<b>Seat</b>	Metal-to-metal	<b>Rangeability</b>	Class IV (0.01% of Cv)
<b>Packing</b>	Ethylene propylene O-ring	<b>Leakage Rate</b>	
<b>Mounting</b>	NEMA 1 (interior only)		
<b>Flow characteristics:</b> <b>Two-way valves</b> <b>Three-way valves</b>	Modified equal percentage Linear		

Table 1. Close-Off Ratings.


Action	Line Size Inches (mm)	Flow Rate, Cv (Kvs)	Close-Off Ratings psi (kPa)	Action	Line Size Inches (mm)	Flow Rate, Cv (Kvs)	Close-Off Ratings psi (kPa)
			Electronic Actuator SSB...				Electronic Actuator SSB...
NC	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	70 (483)	3-Way Mixing, upper	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	70 (483)
	1/2 (15)	2.5 to 4 (2.15 to 3.44)	40 (276)		1/2 (15)	2.5 to 4 (2.15 to 3.44)	40 (276)
	3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)		3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)
NO	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	60 (412)	3-Way Mixing, lower	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	25 (172)
	1/2 (15)	2.5 to 4 (2.15 to 3.44)	35 (241)		1/2 (15)	2.5 to 4 (2.15 to 3.44)	15 (103)
	3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)		3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	10 (69)

Table 2. Valve Dimensions.

### 2-Way Valve



### 3-Way Valve



Size In. (mm)	A	B	C	Weight lbs. (kg)
1/2 (15)	1-3/8 (35)	2-1/4 (57)	1-5/16 (33)	.96 (.44)
3/4 (20)	1-5/8 (41)	2-3/8 (59)	1-5/16 (33)	1.13 (.51)
1 (25)	1-15/16 (49)	2-3/4 (69)	1-9/16 (39)	1.7 (.77)
1/2 (15)	2-3/4 (69)	2-1/4 (74)	1-5/16 (33)	1.10 (0.5)
3/4 (20)	3-1/4 (83)	3-9/16 (90)	1-5/16 (33)	1.44 (.65)
1 (25)	3-7/8 (98)	3-15/16 (99)	1-9/16 (39)	2.20 (1.0)

## Typical Specifications

Automatic control valves shall have NPT threaded type fittings, 1/2-inch through 1-inch (15 mm through 25 mm) sizes, and shall be ANSI rated to withstand the pressures and temperatures encountered. Valves shall have metal-to-metal seats, stainless steel stems, and Ethylene propylene O-ring packing. Valves shall be ANSI Leakage Class IV (0.01% of Cv). Valves shall have a 50:1 rangeability (Cv <1) or better.

All two-way valves shall be provided with equal-percentage contoured throttling plugs. All three-way valves shall be provided with throttling plugs such that the total flow through the valve remains constant (linear) regardless of the valve position.

For complete technical details on two-way valves with union female, angle female, or union male end connections, see *Powermite™ 599 Series, MZ Series Zone Control Unit Two-way Valves Technical Instructions*, Document No. 155-198P25.

Information in this publication is based on current specifications. The company reserves the right to make changes in specifications and models as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners.

© 2009 Siemens Industry, Inc.

**Siemens Industry, Inc.**  
Building Technologies Division  
1000 Deerfield Parkway  
Buffalo Grove, IL 60089  
+ 1 847-215-1000

Your feedback is important to us. If you have  
comments about this document, please send them to  
[sbt\\_technical\\_editor.us.sbt@siemens.com](mailto:sbt_technical_editor.us.sbt@siemens.com)

Document No. 154-012P25  
Printed in the USA  
Page 2 of 2